

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

*What Is Claimed Is:*

1. An assay apparatus, comprising:

5 a temperature adjusting means for simultaneously adjusting a temperature of a plurality of samples in accordance with a pre-determined temperature profile; and

a receiving means for receiving spectral emission from the samples while the temperature of the samples is adjusted in accordance with the temperature profile.

10 2. The apparatus of claim 1, wherein said receiving means receives fluorescent emission.

3. The apparatus of claim or 1, wherein said receiving means receives ultraviolet light.

15 4. The apparatus of claim 1, wherein said receiving means receives visible light.

5. The apparatus of claim 1, wherein said temperature adjusting means comprises:

a temperature adjusting element for adjusting the temperature of said heat conducting block.

6. The apparatus of claim 1, wherein said temperature adjusting means comprises:

5

a heat conducting block;

an adaptor disposed on said heat conducting block, wherein said adaptor is configured to receive a container containing the plurality of samples; and

a temperature adjusting element for adjusting the temperature of said heat conducting block.

10

7. The apparatus of claim 1, further comprising:

a movable platform;

wherein said temperature adjusting means comprises a heat conducting block having a plurality of wells formed therein, each of said plurality of wells configured to receive a container containing one of the plurality of samples;

15

wherein said movable platform is configured to receive a plurality of said heat conducting blocks; and

a temperature adjusting element for adjusting the temperature of said heat conducting block.

8. The apparatus of claim 1, further comprising:

a movable platform;

wherein said temperature adjusting means comprises a heat conducting block adapted to receive a container containing the plurality of samples, wherein said movable platform is configured to receive a plurality of said heat conducting blocks; and

a temperature adjusting element for adjusting the temperature of said heat conducting block.

9. The apparatus of claim 8, wherein said movable platform is a

translatable platform.

10. The apparatus of claim 8, wherein said movable platform is a rotatable platform.

11. The apparatus of claim 1, wherein said receiving means is configured to receive spectral emission from the plurality of samples one sample at a time.

12. The apparatus of claim 1, wherein said receiving means is configured to simultaneously receive spectral emission from more than one sample of the plurality of samples.

13. The apparatus of claim 1, wherein said receiving means is configured to simultaneously receive spectral emission from all of the plurality of samples.

5 14. The apparatus of claim 6, wherein said temperature adjusting means further comprises:

a temperature controller for changing the temperature of said heat conducting block in accordance with the pre-determined temperature profile.

10 15. The apparatus of claim 7, wherein said temperature adjusting means comprises:

a temperature controller for changing the temperature of said heat conducting block in accordance with the pre-determined temperature profile.

15 16. The apparatus of claim 8, wherein said receiving means comprises:  
a light source for emitting an excitatory wavelength of light for the samples; and

a sensor for detecting the spectral emission from the samples in response to the excitatory wavelength of light.

17. The apparatus of claim 1, wherein said receiving means comprises a photomultiplier tube.

18. The apparatus of claim 2, wherein said receiving means comprises a fluorescence scanner.

19. The apparatus of claim 2, wherein said receiving means comprises a fluorescence scanner.

5 20. The apparatus of claim 11, wherein said receiving means comprises a fluorescence scanner.

21. The apparatus of claim 12, wherein said receiving means comprises a fluorescence scanner.

10 22. The apparatus of claim 1, wherein said receiving means comprises a charge coupled device.

23. The apparatus of claim 13, wherein said receiving means comprises a fluorescence imaging camera.

24. The apparatus of claim 22, wherein said receiving means comprises a CCD fluorescence imaging camera.

15 25. The apparatus of claim 1, wherein said receiving means comprises a diode array.

26. An assay apparatus, comprising:

a movable platform;

a plurality of heat conducting blocks disposed on said platform, wherein  
each of said plurality of heat conducting blocks is adapted to receive a plurality  
of samples;

a light source for emitting an excitatory wavelength of light for the  
samples;

a temperature adjusting means for adjusting the temperature of said heat  
conducting blocks, thereby adjusting the temperature of the samples;

a sensor for detecting the spectral emission from the samples in response  
to the excitatory wavelength of light; and

wherein said movable platform is moved between heat conducting blocks  
to sequentially detect spectral emission from the samples in each of said plurality  
of heat conducting blocks.

27. The apparatus to claim 26, wherein said movable platform is a  
translatable platform.

28. The apparatus of claim 26, wherein said movable platform is a  
rotatable platform.

29. The apparatus of claim 26, wherein each of said plurality of heat conducting blocks has a plurality of wells formed therein, each of said plurality of wells configured to receive a container containing one of the plurality of samples.

30. The apparatus of claim 26, wherein each of said plurality of heat conducting blocks is adapted to receive a container containing the plurality of samples.

31. The apparatus of claim 26, wherein said temperature adjusting means comprises:

a temperature controller for changing the temperature of said heat conducting blocks in accordance with a pre-determined temperature profile.

32. The apparatus of claim 26, wherein said sensor comprises a photomultiplier tube.

33. The apparatus of claim 26, wherein said sensor comprises a fluorescence scanner.

34. The apparatus of claim 33, wherein said fluorescence scanner is configured to scan the plurality of samples one sample at a time.



35. The apparatus of claim 33, wherein said fluorescence scanner is configured to simultaneously scan a subset of at least two of the plurality of samples.

5 36. The apparatus of claim 33, wherein said receiving means is configured to simultaneously receive spectral emission from all of the plurality of samples.

37. The apparatus of claim 36, wherein said receiving means comprises a fluorescence imaging camera.

10 38. The apparatus of claim 26, wherein said sensor comprises a charge-coupled device.

39. The apparatus of claim 38, wherein said sensor comprises a charge-coupled device camera.

15 40. The apparatus of claim 26, wherein said sensor comprises a diode array.

41. The apparatus of claim 37, wherein said fluorescence imaging camera is configured to simultaneously scan all of the plurality of samples in one of said heat conducting blocks.

42 The apparatus of claim 37, wherein said fluorescence imaging camera is configured to simultaneously scan all of the plurality of samples in all of said plurality heat conducting blocks.

5 43 The apparatus of claim 39, wherein said charged coupled device camera is configured to simultaneously scan all of the plurality of samples in one of said heat conducting blocks.

44. The apparatus of claim 39, wherein said charge coupled device camera is configured to simultaneously scan all of the plurality of samples in all of said plurality heat conducting blocks.

10 45. The apparatus of claim 26, wherein at least one sample of the plurality of samples comprises a biological polymer.

46. The apparatus of claim 26, wherein at least one sample of the plurality of samples comprises a protein.

15 47. The apparatus of claim 26, wherein at least one sample of the plurality of samples comprises a nucleic acid.

48. The apparatus of claim 1, further comprising:  
a computer controller for controlling the operation of said temperature  
adjusting means.

49. The apparatus of claim 14, wherein said temperature controller  
comprises a processor.

50. The apparatus of claim 15, wherein said temperature controller  
comprises a processor.

51. The apparatus of claim 31, wherein said temperature controller  
comprises a processor.

52. The apparatus of claim 26, wherein said temperature adjusting  
means independently adjusts the temperature of each of said heat conducting  
blocks.

53. An assay apparatus, comprising:  
a heating means for simultaneously heating a plurality of samples; and  
a receiving means for receiving spectral emission from the samples while  
the samples are being heated.